



MCS : MIR Camera & Spectrometer



nickname wanted

MCS Team:

PI: Hirokazu Kataza
co-PI: Takehiko Wada
co-PI: Itsuki Sakon
co-PI: Naoto Kobayashi



General Outline
Wide-field Imager & Spectrograph at 5-38μm
Detectors:
 Si:As 2Kx2K @ 5-6K / Si:Sb 1Kx1K @ ~3K
Channels:
 Wide-field Camera (WFC)
 Medium-Resolution Spectrometer (MRS)
 High-Resolution Spectrometer (HRS)
 Low-Resolution Spectrometer (LRS)
Observing Mode:
 Imaging/spectroscopy with micro-scan/step-scan



Brush up process of the specifications

Successful detector development (High dope Si:As) – Wider LRS-L wavelength coverage
 Failure of immersion grating development – Adopt reflection echelle grating with more weight cost
 Failure of prism development for LRS-L – Limit the wavelength coverage
 Preference order against resource limit (especially weight resource):
 (1)WFC-L and S, (2)HRS-L, (3)MRS-L and S, (4) LRS-L, (5) LRS-S, (6) HRS-S
 We think that MRS-L without MRS-S loose scientific output significantly.

Instrument Specifications

Specifications

WFC	WFC-L	WFC-S
array format	Si:Sb (1k x 1k)	Si:As (2k x 2k)
Wavelength coverage	20-38μm	5-25μm
Filter bands	20-38μm R=10	5-25μm R=5
pixel scale	0''.293 /pix	0''.146 /pix
FOV size	5' X 5'	5' X 5'
Sensitivity (point source, 1hr, 5σ)	4.9 / 6.7 / 7.7 μJy 20 / 30 / 38 μm	0.13 / 1.2 / 3.5 μJy 5 / 10 / 20 μm

LRS	LRS-L	LRS-S
array format	Si:Sb (1k x 1k) Option: Si:As high dope 1kx1k	Si:As (2k x 2k)
Wavelength coverage	20-38μm (option:25-48 μm)	5-26μm
dispenser	Grating or Prism	Prism
Spectral resolution ($R=\lambda/\Delta\lambda$)	50-100	50-100
pixel scale	0''.293 /pix	0''.146 /pix
Slit length x width	2'.5 x 2''.66	2.5' x 1''.40
Sensitivity (point source, 600s, 1σ for low background case)	64 / 84 / 108 / 136 μJy at 20 / 25 / 30 / 35 μm	7.3/14/26/39 μJy at 7.5 / 10 / 15 / 20 μm

MRS	MRS-L	MRS-S
array format	Si:Sb (1k x 1k)	Si:As (2k x 2k)
Wavelength coverage	19.5μm-36.1μm	10-20μm
Spectral resolution ($R=\lambda/\Delta\lambda$)	680@27.8μm	1460@13μm
pixel scale	0''.485 /pix	0''.403 /pix
Slit length x width x slices	12'' x 2''.5 x 5	12'' x 1''.2 x 5
FOV size	12'' x 12''.5	12'' x 6''
Sensitivity (point source, 600s, 1σ for low background case)	~600 μJy	~100 μJy

HRS	HRS-L	HRS-S
array format	Si:As (2k x 2k)	Si:As (2k x 2k)
Wavelength coverage	12μm-18μm	4-8μm
Spectral resolution ($R=\lambda/\Delta\lambda$)	20,000 – 30,000	30,000
pixel scale	0''.48 /pix	0''.288 /pix
Slit length x width	6''.0 x 1''.2	3''.5 x 0''.72
Main disperser	CdTe or KRS5 imm. Grat.	ZnSe immersion Grat.
Sensitivity (point source, 1hr, 5σ)	1.2 mJy	0.8 mJy
Sensitivity (diffuse, 1hr, 5σ)	4.2 MJy/sr	8.2 MJy/sr

Spacecraft Resources

Resources	Current Estimate	System Allocation
Cold Mass	46.9 kg with 20% margin	45 kg with 20% margin
Cold Volume (XYZ) [mm]	N/A	Specified by figure
Heat Lift at 1.7K [mW] (observing/standby)	2.6 / <0.013 (WFC & LRS) 2.6 / <0.013 (WFC & MRS) 1.3 / <0.013 (WFC & HRS) With 30% margin	2.1 / 0.3 with 30% margin
Heat Lift at 4.5K [mW] (observing/standby)	4.7 / 0.24 with 30% margin	4 / 0.4 with 30% margin
Electric Power [W] (observing/standby)	29 W without margin	35 / 35 with TBD margin